

Henry®

#1 CHOICE OF PROFESSIONALS®



ULTRATouch™ R13

RECYCLED DENIM INSULATION

Interior &
Exterior Walls



SUSTAINABILITY MEETS INSULATION


UltraTouch Recycled Denim Insulation, also known as natural cotton fiber insulation, is a high-performance insulation that's made from recycled denim clothing. This insulation is suitable for residential use in the same places as fiberglass or mineral wool batts would be used—between open roof rafters, ceiling joists and wall studs.

- ✓ Eco-Friendly
- ✓ No Itchy Fibers
- ✓ No VOCs
- ✓ Sound Absorption
- ✓ Fire Resistant
- ✓ Resistant to Mold and Mildew
- ✓ Thermal Performance
- ✓ Easy Installation



MADE WITH RECYCLED DENIM

UltraTouch includes 80% post-consumer authentic cotton denim. Each year, 19.5 million pounds of waste is diverted from landfills.



EASY-TEAR PERFORATION

Perforated batts allow for quick and easy off-size cavity installation. Simply measure, tear, fit and you're all done!



SOUND ABSORBING

Using a patented process, recycled cotton denim becomes top-quality insulation, enhancing thermal comfort and reducing noise efficiently.



NO-GLOVES REQUIRED

No fiberglass or chemical irritants means no itch and no need for special gear during installation, ensuring simple, safe, and lasting comfort.

SPECIFICATIONS & PHYSICAL PROPERTIES

PART NUMBER

HER13445

THICKNESS

3.5" (89 mm)

SQUARE FEET

77.52

R-VALUE

13

WIDTH

15" (381 mm)

WEIGHT. LBS.

32

PIECES PER BAG

8

LENGTH

93" (2362 mm)

PROPERTY	PERFORMANCE	TEST METHOD
Surface Burning Characteristics	Class-1	ASTM E-84 / UL-723
Fire Hazard Classification	Class-1	ASTM E-84 / UL-723
Corrosion Resistance	Passed	ASTM C-739
Fungi Resistance	Passed (No Growth)	ASTM C-739
Bacteria Resistance	Passed (No Growth)	ASTM C-739
Moisture Absorption Passed	Passed (<15%)	ASTM C-739
Fire Test of Building Material	Passed (1 Hour Rating)	ASTM E-119/UL-263

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.



The Seal of Cotton and cotton enhanced™ are trademarks of Cotton Incorporated. This product contains a minimum of 80% cotton.



Henry®

#1 CHOICE OF PROFESSIONALS®

Visit Henry.com

UltraTouch® Recycled Denim Insulation

Interior & Exterior Walls



For more information, visit www.henry.com or for technical assistance call us at 800-486-1278. Refer to the Safety Data Sheet prior to using this product. The Safety Data Sheet is available at www.henry.com or by emailing Henry Product Support at productsupport@henry.com or by calling 800-486-1278.